



**Body Type:** H10030ST-2-120-A60GBHW

**The body configuration below is based on these chassis selections (Chassis is not included):** Ford F750 4x2 Ford HD 6-speed Auto 120" CA Diesel

**Factory Options Selected:** Diesel Motor, No Factory Backup Camera, Rear Spring Suspension, Vertical Exhaust, Single Fuel Tank

**Cost Variance Modifier (CVM),** meaning that if inflation continues to accelerate, we will have no choice but to requote prior to line drawing approval and release for production. In the alternative, you may cancel orders (with applicable fees) any time prior to manufacture. Dealers, be sure to include this and notify your customers of the CVM possibility.

**Delivery of service body units and lube units (installed on chassis or ship-out body) are to be arranged by either the selling dealer or end use customer; Maintainer does not arrange shipping of complete units.**

**Chassis Disclaimer:** All information and quote pricing shown with this proposal is based on a design utilizing the chassis make and model along with the specific features and options with the chassis as noted above. If any changes are made to the chassis type or options the proposal must be updated as they could change available unit features and options along with quote pricing. Any changes made without updating the quote will void this proposal.

**Ex-factory delivery:** 360-450 days after receipt of order with full order information subject to prior sales and chassis availability.

Config # C24090

Qty	Item Description
<b>--- Maintainer Body ---</b>	
1	Base price of Service body - 2-ton, 62" tall compartments, 54" x 31" wheel well opening with skirting, front body bulkhead, body access grab handles painted safety yellow (locations and number to vary with design)
14	Feet of Service Body - 2-ton, 62" tall Galvannealed compartments, with reinforced floors, clean out drains, 11 Gauge Deck Plate on Compartment Tops and Backs
1	Factory Installation of body on a chassis. Note: On 2-ton chassis, we will no longer be modifying the dash for lights or switches. Will use OEM switches where applicable, any additional Maintainer switches will be on a bracket / panel mounted in separate location
1	Short Tower Crane reinforcement for MTS 1 or 2 ton service body (up to 75,000 ft*Lbs.)
1	Crane Location : Curb Side
<b>--- Chassis Equipment &amp; Accessories ---</b>	
1	Spring or spacer leveling package added to one side of chassis suspension (2-Ton)
1	2.5 lb ABC fire extinguisher, and hazard reflectors
1	Back up alarm - 97 dB at 1 meter
1	~Camera, NagyFleet, 7" Color monitor, external mount camera with infra-red Note: Monitor mounted to windshield (not on dash)
1	Modify chassis vertical exhaust on F650 & F750 (2016 and newer), In lieu of notching front of body
1	Heater, electric, 120 volt, fan forced, 1,000 / 1,500 watt (014892) - w/ male plug NOTE: May require an additional 120 volt plug-in wired to power source NOTE: Shipped along loose unless otherwise specified
<b>--- Hydraulic Power Package ---</b>	

1	Miller EnPak A60GBHW (Diesel) Power Package with control panel (907815) 24.8HP Kubota diesel engine, uses chassis 12-volt battery & fuel (requires two auxiliary fuel ports). Includes engine block heater with 120V plug-in. Hydraulic Pump: Open Center (10 gpm). Air Compressor: Rotary screw 60 CFM @ 100 PSI. Generator: 7,000 Watt. Welder: 325A DC @ 100% duty cycle. Jumpstart / Charger: 150 AMP 12V/24V battery charger with 12V (300 amp) / 24V (300 amp) boost. Chassis battery charge feature, protection for reverse polarity, correct charge voltage, minimum voltage sensing (.5V min required to activate charging). Jump & Weld output panel mounted next to A60 panel. White housing: 21"W x 27"T x 46.5"L, 800 lbs.
1	Auxiliary Power Unit Notes: Air Tank, Welder Leads, and Jump Cables are not included in kits. Mounting an APU near fixed walls, requires a minimum of 40" width, 66" length for air flow and panel access. Mounting inside an enclosure requires AO-03606 for ventilation. Center deck recommended installation with a removable panel for protection.
1	Crane remote control hook-up (tethered or wireless), for engine-driven power packages
1	Mounting Bracket / Shelf across center deck - Heavy duty, up to 1,200 Lbs. capacity Note: Can be used for APU units with reservoir, Mounting angles are not required
1	28 Gallon Steel Square Reservoir
28	Hydraulic Oil (Standard oil, per gallon) Oil good for -25° F startup and 9° F to 187° F operating temperature
1	No Reservoir Heater was selected.
2	Sealed duplex electrical GFI outlet, 120 volt, Installed & wired to power source
1	Sealed electrical outlet, 240 volt, Installed & wired to power source
1	Hydraulics Note:1- 120v outlet in chassis cab / 1- 120v & 1- 240v outlets out SS rear
	<b>--- Welder / Generator / Inverter / Power Equipment ---</b>
1	~Cables, Welder leads, w/ clamp and stinger, 50' of 1/0, 300 amps
1	Miller Jump start cables (25ft) for APU / welder / gen. with jumpstart option
	<b>--- Air Compressor Equipment &amp; Accessories ---</b>
1	Air tank - 17 gallon - (Pressure rating of 200 psi) / 16" diameter (000012) Includes moisture drain, Painted Black
1	Air accessory package - 1/2" X 50', spring rewind reel, hose & ball stop
1	1/2" Filter, Regulator, and Lubricator (FRL)
1	Fiber box; Hose reel access, Limit 1 Reel Per Fiber box
	<b>--- Outriggers &amp; Accessories ---</b>
1	Outriggers for cranes up to 90,000 ft*Lbs., hydraulic up/down rear outriggers (2) with hydraulic extend in/out on crane side (57" extend) Required with H10030, H10034, H12025, H14025 Cranes
1	Outrigger pads, removable (with storage bracket)
	<b>--- Compartment Equipment &amp; Accessories ---</b>
1	Pressurized Storage System (PSS), 2-blowers with filters
14	Feet of Master Compartment Locking System for service body. Spring loaded with padlock guards for both side packs
	<b>--- Street Side Vertical Compartment #1 ---</b>
1	Dimensions:62" Tall X45" Wide X23" Deep
1	12-Volt LED strip light
1	Vertical Double 3/16" Aluminum Doors (French Style), Includes Rubber Seal
1	Standard Compartment 3-Point "D Ring" Door Latch
2	Door Gas spring 65# (003184)
1	DualLock or Bolt Bin - See configuration details and price below
	<b>--- Street Side Vertical Compartment #2 ---</b>
1	Dimensions:62" Tall X45" Wide X23" Deep
1	12-Volt LED strip light
1	Vertical Double 3/16" Aluminum Doors (French Style), Includes Rubber Seal
1	Standard Compartment 3-Point "D Ring" Door Latch
2	Door Gas spring 65# (003184)

2	Shelf, aluminum adjustable compartment shelf (250 Lbs. capacity) - Installed
	<b>--- Street Side Overwheel Compartment ---</b>
1	Dimensions:31" Tall X54" Wide X23" Deep
1	12-Volt LED strip light
1	Vertical Double 3/16" Aluminum Doors (French Style), Includes Rubber Seal
1	Standard Compartment 3-Point "D Ring" Door Latch
2	Door Gas spring 65# (003184)
1	Shelf, aluminum adjustable compartment shelf (250 Lbs. capacity) - Installed
	<b>--- Street Side Rear Vertical Compartment ---</b>
1	Dimensions:62" Tall X24" Wide X23" Deep
1	12-Volt LED strip light
1	Single 3/16" Aluminum Vertical hinge door, Includes Rubber Seal
1	Standard Compartment 3-Point "D Ring" Door Latch
1	Door Gas spring 65# (003184)
1	DuaLock or Bolt Bin - See configuration details and price below
	<b>--- Curb Side Vertical Compartment #1 ---</b>
1	Dimensions:62" Tall X35" Wide X23" Deep
1	12-Volt LED strip light
1	Vertical Double 3/16" Aluminum Doors (French Style), Includes Rubber Seal
1	Standard Compartment 3-Point "D Ring" Door Latch
2	Door Gas spring 65# (003184)
2	Shelf, aluminum adjustable compartment shelf (250 Lbs. capacity) - Installed
	<b>--- Curb Side Vertical Compartment #2 ---</b>
1	Dimensions:62" Tall X35" Wide X23" Deep
1	12-Volt LED strip light
1	Vertical Double 3/16" Aluminum Doors (French Style), Includes Rubber Seal
1	Standard Compartment 3-Point "D Ring" Door Latch
2	Door Gas spring 65# (003184)
2	Shelf, aluminum adjustable compartment shelf (250 Lbs. capacity) - Installed
	<b>--- Curb Side Vertical Compartment #3 ---</b>
1	Dimensions:62" Tall X20" Wide X23" Deep
1	Single 3/16" Aluminum Vertical hinge door, Includes Rubber Seal
1	Standard Compartment 3-Point "D Ring" Door Latch
1	Door Gas spring 65# (003184)
1	12-Volt LED strip light
1	2 Oxy/Act Bottle Storage Kit, contains Ratchet Strap, Vents in door,(2) "J" Hooks, reinforced floor (Protective spray coated) and mounting side brackets
	<b>--- Curb Side Overwheel Compartment ---</b>
1	Dimensions:31" Tall X54" Wide X23" Deep
1	12-Volt LED strip light
1	Vertical Double 3/16" Aluminum Doors (French Style), Includes Rubber Seal
1	Standard Compartment 3-Point "D Ring" Door Latch
2	Door Gas spring 65# (003184)
1	Shelf, aluminum adjustable compartment shelf (250 Lbs. capacity) - Installed
	<b>--- Curb Side Crane Pedestal ---</b>
1	Dimensions:51" Tall X24" Wide X23" Deep
1	12-Volt LED strip light

1	Single 3/16" Aluminum Vertical hinge door, Includes Rubber Seal
1	Standard Compartment 3-Point "D Ring" Door Latch
1	Door Gas spring 65# (003184)
2	Shelf, aluminum adjustable compartment shelf (250 Lbs. capacity) - Installed
<b>--- Lighting / Electrical Equipment &amp; Accessories ---</b>	
1	Base electrical components - Can System Includes Wiring Harnesses, Power Distribution Module, & Main Body Controller
1	4.3" display CAN switch panel
1	~Grote FMVSS 108 LED lighting / reflector Kit: (2) Oval S/T/T/R, (2) Oval S/T/T, (5) Red 3/4" Marker lights, (2) Amber 3/4" Marker lights
5	Exterior 12-Volt LED flood light 022232 ( 2,100 Lumens)
1	~Exterior 12-Volt LED remote Maxxima flood light 022233 (2,100 lumens) Includes magnetic base and 30' cord
2	12-Volt Plug-in, receptacle for remote or portable flood light, installed (each)
1	~Strobe Lighthoods, L.E.D, oval, amber, recessed, 6.5" x 2.25" (pair)
1	~Light Bar, Whelen amber Lo-Profile LED mini light bar, Model MC16PA (#019873) 2-3/8" H x 16-1/2" W x 7-3/4" D
1	Light bar mounting plate, includes wire loom holders
1	Light Bar Mount (Aluminum), front of body, center deck width, tube frame, no panel Includes protective spray coating
1	Exterior Lighting Note:2- out each side & 1- out SS rear
<b>--- Paint, Undercoating, &amp; Protective Spray Coating (PSC) ---</b>	
14	Feet of Unit Painted Urethane "White" color. Not a base coat/clear coat or Metallic
14	Feet of Primer
14	Feet of Splatter Coating on interior of compartments
14	Feet of Undercoat
1	PSC- Level 30 •Compartment Fronts •Bottoms of Door Frames •Outside area of Wheel Wells •Outer Vertical outrigger tubes •Bumper Sides & Step (face & top) •Bumper Top Surface •Bumper Vertical Surface •Center Deck Floor, includes Welder Deck •Cargo Side Walls, includes Bulkhead •Compartment Tops, includes Welded on brackets/Guards
<b>--- Center Deck Equipment &amp; Accessories ---</b>	
1	Center Deck Dimensions:168" Long X49" Wide X1/8" Thickness
14	~1/8" Cargo floor (deck plate)
1	10" Tall hinge-down "Slam Latch" Aluminum tailgate (12" total Height, 10" tall above deck) (protective spray front, black paint on rear)
6	Flush mount "D" ring tie-downs in bed floor #003217, each
<b>--- Rear Bumper &amp; Accessories ---</b>	
1	26" steel workbench bumper with recessed step on curb side, 1 storage compartment. Includes: Bolt on Yellow grab handles and strip light for recessed step safety
1	~Bumper surface 3/16" smooth
1	~Transverse bar storage compartment in workbench bumper flush to the floor
1	Vise / grinder removable mounting plate HD, includes drain slots in plate
1	Class IV hitch receiver - 2" receiver - rated at 1,500 Lbs.. vert. 10,000 Lbs. Includes Safety Chain loops MGTW Note: customer is responsible to verify tow rating of chassis and available GVWR/GCWR remaining after loading of body and all other items.
1	Trailer plug-in 7-prong flat blade #007486 (RV style)
1	Step, Bolt-on, flexible sides with stainless steel step, Painted Safety Yellow #026127 (standard step)
<b>--- Miscellaneous Equipment &amp; Accessories ---</b>	
1	Single axle wheel well extensions (3-piece bolt-on),aluminum w/ protective spray. Note: Kit includes flares for both sides of body
1	Mud flaps, 2-ton, "Maintainer"
1	Mud flap bracket for a 20" mudflap

1	Parts and service manual (Online & condensed paper version)
---	---

**---Maintainer Crane---**

**Config # C24091**

Qty	Item Description
1	H10030ST Crane 10,000 Lbs. max capacity (60,000 ft*Lbs.) with hydraulic extend hex-boom 13'-30' Note: Max capacity listed above is for 2-part line, for single-part line max capacity is 5,000 Lbs. Crane includes A2B, overload system, holding valves Note: Requires 90,000 ft*Lbs. outriggers with 57" extension, maximum pedestal height = 31" Note: Maximum pedestal height = 31" Paint note: Ship-out crane-only: Requires additional paint charge Crane installed on body: No additional paint charge unless different color than body MIN GVW REQUIRED : 26,000
1	Install hydraulic crane on body - includes boom saddle, and valve well with HD reinforced cover
1	~Load Block (No live swivel) H6-H10
1	Planetary winch (H8 / H10030)
1	Crane remote, wireless, push button (H6-H14), with true independent proportional control, includes holder, external antenna, hour meter, engine start/stop
1	Backup cable for wireless crane remote, 35ft (#022585)
1	Annual crane inspection (initial inspection)
1	Paint Crane to match Service Body
1	Exterior 12v LED flood light on crane boom tip (2-Lights, Ecco E92006, 1365 Lumens) on pivot bracket

**---Street Side Vertical #1 Dualock---**

Config # C24092 Design Style: Custom Dualock Configuration

**Housing Dimensions:41.5" Tall, 39" Wide, 18" Deep**

***Top Shelf is Standard, Drawers Listed from Top to Bottom***

Drawer #	Height	Dividers
Drawer 1	3"	Side to Side
Drawer 2	3"	Side to Side
Drawer 3	3"	Side to Side
Drawer 4	5"	Side to Side
Drawer 5	5"	Side to Side
Drawer 6	5"	Side to Side
Drawer 7	7"	Side to Side

*BOTTOM SPACE: 7.0 Inches Tall*

**---Street Side Rear Vertical Dualock---**

Config # C24093 Design Style: (5) drawer set #013225 (18" wide)

**Housing Dimensions:30" Tall, 18" Wide, 18" Deep**

***Top Shelf is Standard, Drawers Listed from Top to Bottom***

Drawer #	Height	Dividers
Drawer 1	4"	Front to Back
Drawer 2	4"	Front to Back
Drawer 3	4"	Front to Back
Drawer 4	4"	Front to Back
Drawer 5	4"	Front to Back

*BOTTOM SPACE: 7.0 Inches Tall*