



Body Type: H8524ST-2-84

The body configuration below is based on these chassis' selections: Ford F650 4x2 Ford HD 6-speed Auto 84" CA Diesel

Factory Options Selected: Diesel Motor, No Factory Backup Camera, Rear Spring Suspension, Vertical Exhaust, Single Fuel Tank

Cost Variance Modifier (CVM), meaning that if inflation continues to accelerate, we will have no choice but to requote prior to line drawing approval and release for production. In the alternative, you may cancel orders (with applicable fees) any time prior to manufacture. Dealers, be sure to include this and notify your customers of the CVM possibility.

Delivery of service body units and lube units (installed on chassis or ship-out body) are to be arranged by either the selling dealer or end use customer; Maintainer does not arrange shipping of complete units.

Chassis Disclaimer: All information and quote pricing shown with this proposal is based on a design utilizing the chassis make and model along with the specific features and options with the chassis as noted above. If any changes are made to the chassis type or options, the proposal must be updated as they could change available unit features and options along with quote pricing. Any changes made without updating the quote will void this proposal.

Ex-factory delivery: 360-450 days after receipt of order with full order information subject to prior sales and chassis availability.

Config # C24094

Qty	Item Description
--- Maintainer Body ---	
1	Base price of Service body - 2-ton, 62" tall compartments, 54" x 31" wheel well opening with skirting, front body bulkhead, body access grab handles painted safety yellow (locations and number to vary with design)
11	Feet of Service Body - 2-ton, 62" tall Galvannealed compartments, with reinforced floors, clean out drains, 11 Gauge Deck Plate on Compartment Tops and Backs
1	Factory Installation of body on a chassis. Note: On 2-ton chassis, we will no longer be modifying the dash for lights or switches. Will use OEM switches where applicable, any additional Maintainer switches will be on a bracket / panel mounted in separate location
1	Short Tower Crane reinforcement for MTS 1 or 2 ton service body (up to 75,000 ft*Lbs.)
1	Crane Location : Curb Side
--- Chassis Equipment & Accessories ---	
1	Spring or spacer leveling package added to one side of chassis suspension (2-Ton)
1	Electronic engine speed control - computer set - electronic engine
1	2.5 lb ABC fire extinguisher, and hazard reflectors
1	Back up alarm - 97 dB at 1 meter
1	~Camera, NagyFleet, 7" Color monitor, external mount camera with infra-red Note: Monitor mounted to windshield (not on dash)
1	Modify chassis vertical exhaust on F650 & F750 (2016 and newer), In lieu of notching front of body
--- Hydraulic Power Package ---	
1	Closed center LS hydraulic power package W/ HP Filter

1	Closed center load sensing piston pump - std. displacement
1	Oil reservoir - complete #022265, composite 28 gallons; Tank only, excluding oil
28	Hydraulic Oil (Standard oil, per gallon) Oil good for -25° F startup and 9° F to 187° F operating temperature
1	Relocate existing chassis TCM and Fuel / Water separator to allow space for PTO driveline Note: For 2016 Ford F650 / F750 chassis with CCLS hydra-packages (not required for open-center systems)
1	No Reservoir Heater was selected.
1	PTO for electric-over-hydraulic required on chassis with automatic transmission. (Ford F450-F550-F600, F650-F750 & Ram 4500-5500)
--- Welder / Generator / Inverter / Power Equipment ---	
1	Mounting angles, 45" long Includes mounting holes for common welder types (contact factory for compatible welders)
--- Air Compressor Equipment & Accessories ---	
1	Vanair Reliant RC40 reciprocating hydraulic driven 40 CFM air compressor with cover 40 CFM @ 100 PSI / 40 CFM @ 150 PSI with integral hydraulic oil cooler Includes cold weather package (oil cooler thermal bypass) Note: White housing Note: Hydraulic requirement = 12 GPM
1	Mounting angles for Air Compressor
1	Air tank - 17 gallon - (Pressure rating of 200 psi) / 16" diameter (000012) Includes moisture drain, Painted Black
1	Air accessory package - 1/2" X 50', spring rewind reel, hose & ball stop
1	1/2" Filter, Regulator, and Lubricator (FRL)
1	Fiber box; Hose reel access, Limit 1 Reel Per Fiber box
--- Outriggers & Accessories ---	
1	Outriggers for cranes up to 75,000 ft*Lbs., hydraulic up/down rear outriggers (2) with hydraulic extend in/out on crane side (48" extend)
1	Outrigger pads, removable (with storage bracket)
--- Compartment Equipment & Accessories ---	
1	Pressurized Storage System (PSS), 2-blowers with filters
11	Feet of Master Compartment Locking System for service body. Spring loaded with padlock guards for both side packs
--- Street Side Vertical Compartment #1 ---	
1	Dimensions:62" Tall X54" Wide X23" Deep
2	12-Volt LED strip light
1	Vertical Double 3/16" Aluminum Doors (French Style), Includes Rubber Seal
1	Standard Compartment 3-Point "D Ring" Door Latch
2	Door Gas spring 65# (003184)
1	Divider, Vertical, inside compartment
2	Shelf, aluminum adjustable compartment shelf (250 Lbs. capacity) - Installed
1	DuaLock or Bolt Bin - See configuration details and price below
--- Street Side Overwheel Compartment ---	
1	Dimensions:31" Tall X54" Wide X23" Deep
1	12-Volt LED strip light
1	Vertical Double 3/16" Aluminum Doors (French Style), Includes Rubber Seal
1	Standard Compartment 3-Point "D Ring" Door Latch
2	Door Gas spring 65# (003184)
1	Shelf, aluminum adjustable compartment shelf (250 Lbs. capacity) - Installed
--- Street Side Rear Vertical Compartment ---	
1	Dimensions:62" Tall X24" Wide X23" Deep
1	12-Volt LED strip light
1	Single 3/16" Aluminum Vertical hinge door, Includes Rubber Seal

1	Standard Compartment 3-Point "D Ring" Door Latch
1	Door Gas spring 65# (003184)
1	DualLock or Bolt Bin - See configuration details and price below
--- Curb Side Vertical Compartment #1 ---	
1	Dimensions:62" Tall X35" Wide X23" Deep
1	12-Volt LED strip light
1	Single 3/16" Aluminum Vertical hinge door, Includes Rubber Seal
1	Standard Compartment 3-Point "D Ring" Door Latch
1	Door Gas spring 65# (003184)
2	Shelf, aluminum adjustable compartment shelf (250 Lbs. capacity) - Installed
--- Curb Side Vertical Compartment #2 ---	
1	Dimensions:62" Tall X19" Wide X23" Deep
1	Reverse Hinged 3/16" Aluminum, Single Door, Included Rubber Seal
1	Standard Compartment 3-Point "D Ring" Door Latch
1	Door Gas spring 65# (003184)
1	12-Volt LED strip light
1	2 Oxy/Act Bottle Storage Kit, contains Ratchet Strap, Vents in door,(2) "J" Hooks, reinforced floor (Protective spray coated) and mounting side brackets
--- Curb Side Overwheel Compartment ---	
1	Dimensions:31" Tall X54" Wide X23" Deep
1	12-Volt LED strip light
1	Vertical Double 3/16" Aluminum Doors (French Style), Includes Rubber Seal
1	Standard Compartment 3-Point "D Ring" Door Latch
2	Door Gas spring 65# (003184)
1	Shelf, aluminum adjustable compartment shelf (250 Lbs. capacity) - Installed
--- Curb Side Crane Pedestal ---	
1	Dimensions:55" Tall X24" Wide X23" Deep
1	12-Volt LED strip light
1	Single 3/16" Aluminum Vertical hinge door, Includes Rubber Seal
1	Standard Compartment 3-Point "D Ring" Door Latch
1	Door Gas spring 65# (003184)
2	Shelf, aluminum adjustable compartment shelf (250 Lbs. capacity) - Installed
--- Lighting / Electrical Equipment & Accessories ---	
1	Base electrical components - Can System Includes Wiring Harnesses, Power Distribution Module, & Main Body Controller
1	4.3" display CAN switch panel
1	~Grote FMVSS 108 LED lighting / reflector Kit: (2) Oval S/T/T/R, (2) Oval S/T/T, (5) Red 3/4" Marker lights, (2) Amber 3/4" Marker lights
6	Exterior 12-Volt LED flood light 022232 (2,100 Lumens)
1	~Strobe Lightheads, L.E.D, oval, amber, recessed, 6.5" x 2.25" (pair)
1	~Light Bar, Whelen amber Lo-Profile LED mini light bar, Model MC16PA (#019873) 2-3/8" H x 16-1/2" W x 7-3/4" D
1	Light bar mounting plate, includes wire loom holders
1	Light Bar Mount (Aluminum), front of body, center deck width, tube frame, no panel Includes protective spray coating
1	Exterior Lighting Note:2-out each side & rear
--- Paint, Undercoating, & Protective Spray Coating (PSC) ---	
11	Feet of Unit Painted Urethane "White" color. Not a base coat/clear coat or Metallic
11	Feet of Primer

11	Feet of Splatter Coating on interior of compartments
11	Feet of Undercoat
1	PSC- Level 30 •Compartment Fronts •Bottoms of Door Frames •Outside area of Wheel Wells •Outer Vertical outrigger tubes •Bumper Sides & Step (face & top) •Bumper Top Surface •Bumper Vertical Surface •Center Deck Floor, includes Welder Deck •Cargo Side Walls, includes Bulkhead •Compartment Tops, includes Welded on brackets/Guards
--- Center Deck Equipment & Accessories ---	
1	Center Deck Dimensions:132" Long X49" Wide X1/8" Thickness
11	~1/8" Cargo floor (deck plate)
1	10" Tall hinge-down "Slam Latch" Aluminum tailgate (12" total Height, 10" tall above deck) (protective spray front, black paint on rear)
4	Flush mount "D" ring tie-downs in bed floor #003217, each
--- Rear Bumper & Accessories ---	
1	26" steel workbench bumper with recessed step on curb side, 1 storage compartment. Includes: Bolt on Yellow grab handles and strip light for recessed step safety
1	~Bumper surface 3/16" smooth
1	~Transverse bar storage compartment in workbench bumper flush to the floor
1	Vise / grinder removable mounting plate HD, includes drain slots in plate
1	Class IV hitch receiver - 2" receiver - rated at 1,500 Lbs.. vert. 10,000 Lbs. Includes Safety Chain loops MGTW Note: customer is responsible to verify tow rating of chassis and available GVWR/GCWR remaining after loading of body and all other items.
1	Trailer plug-in 7-prong flat blade #007486 (RV style)
1	Step, Bolt-on, flexible sides with stainless steel step, Painted Safety Yellow #026127 (standard step)
--- Miscellaneous Equipment & Accessories ---	
1	Single axle wheel well extensions (3-piece bolt-on),aluminum w/ protective spray. Note: Kit includes flares for both sides of body
1	Mud flaps, 2-ton, "Maintainer"
1	Mud flap bracket for a 20" mudflap
1	Parts and service manual (Online & condensed paper version)
---Maintainer Crane---	
Config # C24095	
Qty	Item Description
1	H8524ST Crane 8,500 Lbs. max capacity (52,500 ft*Lbs.) with hydraulic extend hex-boom 13'-24' Note: Max capacity listed above is for 2-part line, for single-part line max capacity is 5,000 Lbs. MIN GVW REQUIRED: 19,500. Requires outrigger package (AO-50751)
1	Install hydraulic crane on body - includes boom saddle, and valve well with HD reinforced cover
1	~Load Block (No live swivel) H6-H10
1	Planetary winch (H8 / H10030)
1	Crane remote, wireless, push button (H6-H14), with true independent proportional control, includes holder, external antenna, hour meter, engine start/stop
1	Backup cable for wireless crane remote, 35ft (#022585)
1	Annual crane inspection (initial inspection)
1	Paint Crane to match Service Body
1	Exterior 12v LED flood light on crane boom tip (2-Lights, Ecco E92006, 1365 Lumens) on pivot bracket

---Street Side Vertical #1 Dualock---

Config # C24096 Design Style: (7) drawer set #020017 (29" wide)

Housing Dimensions:41.5" Tall, 29" Wide, 18" Deep

Top Shelf is Standard, Drawers Listed from Top to Bottom

Drawer #	Height	Dividers
Drawer 1	3"	Side to Side
Drawer 2	3"	Side to Side
Drawer 3	3"	Side to Side
Drawer 4	5"	Side to Side
Drawer 5	5"	Side to Side
Drawer 6	5"	Side to Side
Drawer 7	7"	Side to Side

BOTTOM SPACE: 7.0 Inches Tall

---Street Side Rear Vertical Dualock---

Config # C24097 Design Style: (5) drawer set #022507 (24" wide)

Housing Dimensions:30" Tall, 24" Wide, 18" Deep

Top Shelf is Standard, Drawers Listed from Top to Bottom

Drawer #	Height	Dividers
Drawer 1	4"	Side to Side
Drawer 2	4"	Side to Side
Drawer 3	4"	Side to Side
Drawer 4	4"	Side to Side
Drawer 5	4"	Side to Side

BOTTOM SPACE: 7.0 Inches Tall